



EXCEED SAE 100 R2 AT TYPE S, EN 853 – 2SN ISO 1436-1
PREMIUM HIGH TEMP.

Part No.	DN	Nominal ID		Nominal OD		Working Pressure		Min. Bend Radius		UOM
		mm	In.	mm	In.	BAR	PSI	mm	In.	
R2-1/4"	6	6.4	0.25	15.2	0.6	400	5,800	102	4.02	Feet
R2-3/8"	10	9.7	0.38	19.1	0.75	345	5,000	125	4.92	Feet
R2-1/2"	12	12.7	0.5	22.1	0.87	293	4,250	180	7.09	Feet
R2-5/8"	16	16	0.63	25.2	0.99	250	3,650	205	8.07	Feet
R2-3/4"	19	19.1	0.75	29.5	1.16	215	3,125	240	9.45	Feet
R2-1"	25	25.4	1	37.9	1.49	175	2,550	300	11.81	Feet
R2-1.1/4"	31	31.8	1.25	48.8	1.92	155	2,250	420	16.54	Feet
R2-1.1/2"	38	38.1	1.5	54.6	2.15	125	1,800	500	19.68	Feet
R2-2"	51	50.8	2	67.8	2.67	105	1,525	630	24.8	Feet

Tube :

- Elastomer , resistant to hydraulic fluids.

Reinforcement :

- Two braid of high tensile steel wire.

Cover :

- Elastomer , MSHA Approved,

Temperature Range (Medium) :

- -40° C to 150° C