



STEAM HOSE TYPE - 2 (SINGLE WIRE BRAIDED)

Part No.	DN	HOSE ID	HOSE OD	Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius	UOM
		mm	mm	BAR	PSI	BAR	PSI	mm	
R1-3/8"	10	9.5	18.9	10	145	100	1,450	130	Meter
R1-1/2"	12	12.7	22.0	10	145	100	1,450	180	Meter
R1-5/8"	16	15.9	25.4	10	145	100	1,450	200	Meter
R1-3/4"	19	19	28.7	10	145	100	1,450	240	Meter
R1-1"	25	25.4	35.9	10	145	100	1,450	300	Meter
R1-1.1/4"	31	31.8	43.5	10	145	100	1,450	400	Meter
R1-1.1/2"	38	38.1	50.5	10	145	100	1,450	500	Meter
R1-2"	51	50.8	63.5	10	145	100	1,450	650	Meter

Highlights : Suitable for use with saturated steam application.

Tube :

- Synthetic rubber, saturated steam & heat resistant

Reinforcement :

- One braid of high tensile steel wire.

Cover :

- Steam & heat resistant synthetic rubber.

Temperature Range (Medium) :

- -40° C to 195° C